# NSN 5930-00-482-2088

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-482-2088

## Thread Class:

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

1.688 inches

#### **Overall Height:**

1.188 inches

#### **Overall Width:**

1.188 inches

#### First Flat Length:

0.218 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.750 inches single actuator

## Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

#### Operating Tempurature Range:

-65.0/+125.0 degrees celsius

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

3 single section rear

#### Throw Quantity:

4 single section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

## **Rotor Through Connection Quantity:**

3 single section

#### Switch Actuator Indexing Position Quantity:

4 single actuator

# NSN 5930-00-482-2088

Rotary Switch - Page 2 of 2



#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load dc at sea level

#### Style Designator:

Square wafer, panel mount

#### **Test Data Document:**

81349-mil-s-3786/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A052b0