

View Online at <https://aerobasegroup.com/nsn/5930-00-482-5774>

Overall Length:

3.160 inches

Overall Width:

1.550 inches

Mounting Slot Width:

0.203 inches

Capillary Tube Length:

24.0 inches

Bulb Length:

7.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.266 inches

Longest Vertical Distance Between Mounting Centers:

2.000 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

90.0 degrees fahrenheit

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.8 amperes resistive load single voltage and 3.0 amperes inductive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+90.00 actuation point degrees fahrenheit and +58.50/+88.50 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0