## NSN 5930-00-483-2118

Pressure Switch - Page 1 of 2

Cylindrical w/mounting lugs



View Online at https://aerobasegroup.com/nsn/5930-00-483-2118

Thread Class:
3b single pressure connection
Overall Length:
4.200 inches
Overall Height:
1.500 inches
Overall Width:
1.120 inches
Body Diameter:
1.440 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.438 inches
Operating Tempurature Rating:
Between 65.0 degrees celsius and 275.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.4375 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.0 amperes lamp load single voltage
Contact Adjustability:
Contact Adjustability:  Deactuation point not adjustable
Deactuation point not adjustable
Deactuation point not adjustable  Contact Stimulus Rating:
Deactuation point not adjustable  Contact Stimulus Rating:  200.00 actuation point pounds per square inch and 250.00 actuation point pounds per square inch
Deactuation point not adjustable  Contact Stimulus Rating:  200.00 actuation point pounds per square inch and 250.00 actuation point pounds per square inch  Contact Voltage Rating In Volts:
Deactuation point not adjustable  Contact Stimulus Rating:  200.00 actuation point pounds per square inch and 250.00 actuation point pounds per square inch  Contact Voltage Rating In Volts:  28.0 dc at sea level single voltage

## NSN 5930-00-483-2118

Pressure Switch - Page 2 of 2



Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A048b0