

View Online at <https://aerobasegroup.com/nsn/5930-00-484-4189>

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.424 inches

First Flat Length:

0.417 inches single actuator and 0.457 inches single actuator

Flat Height:

0.204 inches single actuator and 0.224 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.834 inches single actuator and 0.914 inches single actuator

Overall Diameter:

1.036 inches

Nonturn Device Radius:

0.360 inches at 3: 00 o'clock and 0.390 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

4 each section front

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Shaft Flat/slot Angular Location:

216.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0