

View Online at <https://aerobasegroup.com/nsn/5930-00-484-5300>

Thread Class:

3b single pressure connection

Overall Length:

3.469 inches

Overall Height:

6.563 inches

Overall Width:

2.656 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

Pressure Switch Type:

Gage

Mounting Method:

Surface

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Decrease

Proof Pressure:

100.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+75.00 actuation point pounds per square inch and +5.00/+90.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0