NSN 5930-00-484-5300

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-484-5300

Thread Class:
3b single pressure connection
Overall Length:
3.469 inches
Overall Height:
6.563 inches
Overall Width:
2.656 inches
Longest Horizontal Distance Between Mounting Centers:
2.719 inches
Longest Vertical Distance Between Mounting Centers:
2.719 inches
Pressure Switch Type:
Gage
Mounting Method:
Surface
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
100.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
500.0 milliamperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+1.00/+75.00 actuation point pounds per square inch and +5.00/+90.00 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts: 600.0 ac at sea level first voltage

NSN 5930-00-484-5300

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0