

View Online at <https://aerobasegroup.com/nsn/5930-00-484-8124>

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.802 inches and 1.822 inches

**Body Length:**

Between 2.230 inches and 2.270 inches

**Body Width:**

0.875 inches

**Body Height:**

Between 1.185 inches and 1.215 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

Between 0.777 inches and 0.807 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Adapter Style:**

Roller plunger

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

Between 40.0 ounces and 72.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0