

View Online at <https://aerobasegroup.com/nsn/5930-00-484-8124>

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.802 inches and 1.822 inches

Body Length:

Between 2.230 inches and 2.270 inches

Body Width:

0.875 inches

Body Height:

Between 1.185 inches and 1.215 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

Between 0.777 inches and 0.807 inches

Actuator Roller Diameter:

0.375 inches

Actuator Adapter Style:

Roller plunger

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

Between 40.0 ounces and 72.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 7.500 amperes inductive dc and 7.500 amperes lamp dc

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0