NSN 5930-00-485-5126

Thermostatic Switch - Page 1 of 2

Overall Length: 1.200 inches Overall Height: 0.500 inches Body Diameter: 0.640 inches



View Online at https://aerobasegroup.com/nsn/5930-00-485-5126

Mounting Slot Width:
0.140 inches
Body Height:
0.325 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -80.0 degrees fahrenheit and 350.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole and slot
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
Nonpile-up Contact Arrangement: 1 pole, single throw, normally open, momentary action
1 pole, single throw, normally open, momentary action
1 pole, single throw, normally open, momentary action Terminal Type:
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability:
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating:
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 215.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 215.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 215.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage
1 pole, single throw, normally open, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 500.0 milliamperes resistive load third voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 215.00 actuation point degrees fahrenheit and 185.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Frequency In Hertz:

NSN 5930-00-485-5126

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0