

View Online at <https://aerobasegroup.com/nsn/5930-00-485-5811>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.469 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

2.750 inches

**First Flat Length:**

0.468 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

2.000 inches

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Slotted bushing at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

18 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

18 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks 1st section front

**Switch Actuator Positioning Increment:**

20.0 degrees single actuator

**Contact Load Current Rating:**

3.0 amperes resistive load dc at sea level and 2.0 amperes inductive load dc at sea level and 2.0 amperes lamp load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0