NSN 5930-00-486-6163

Rotary Switch - Page 1 of 2

Thread Class:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-486-6163

Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.750 inches **Overall Height:** 1.312 inches **Overall Width:** 1.188 inches First Flat Length: 0.250 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.875 inches single actuator **Individual Section Quantity: Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 6 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Shaft Flat/slot Angular Location:** 15.0 degrees from nonturn device single actuator **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug

NSN 5930-00-486-6163

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0