NSN 5930-00-486-7082

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-486-7082 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 3.813 inches **Overall Height:** 1.250 inches **Overall Width:** 0.750 inches **Bushing Length:** 0.500 inches **Body Length:** 1.938 inches **Body Width:** 0.750 inches **Body Height:** 1.250 inches **Actuator Style:** Round **Actuator Diameter:** 0.312 inches **Actuator Height:** 1.000 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Maximum Voltage Rating In Volts:** 125.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 20 **Pile-up Contact Form Arrangement:**

2a1b1c single position

Thread Size:

0.500 inches

NSN 5930-00-486-7082

Lever Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Thread Series Designator:
Unf
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:

N/a **Unit Of Measure:**

Demilitarization:

No

Fiig:

A053a0