

View Online at <https://aerobasegroup.com/nsn/5930-00-486-7099>

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

2.000 inches

Overall Height:

0.886 inches

Body Diameter:

1.181 inches

Mounting Slot Width:

0.172 inches

Body Height:

0.536 inches

Distance Between Mounting Facility Centers:

1.686 inches

Temperature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and slot

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

25.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

56.00 actuation point degrees fahrenheit and 66.00 actuation point degrees fahrenheit and 36.00 deactuation point degrees fahrenheit and 46.00 deactuation point degrees fahrenheit and 20.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0