

View Online at <https://aerobasegroup.com/nsn/5930-00-486-7099>

**Hazardous Locations/environmental Protection:**

Dustproof and moisture proof

**Overall Length:**

2.000 inches

**Overall Height:**

0.886 inches

**Body Diameter:**

1.181 inches

**Mounting Slot Width:**

0.172 inches

**Body Height:**

0.536 inches

**Distance Between Mounting Facility Centers:**

1.686 inches

**Temperature Sensing Element Type:**

Internal sensor

**Mounting Method:**

Bracket and slot

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

25.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

56.00 actuation point degrees fahrenheit and 66.00 actuation point degrees fahrenheit and 36.00 deactuation point degrees fahrenheit and 46.00 deactuation point degrees fahrenheit and 20.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

120.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0