NSN 5930-00-486-7194

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Thread Class:

Body Style:Bushing mounted

2a



View Online at https://aerobasegroup.com/nsn/5930-00-486-7194

Dustproof
Overall Length:
0.950 inches
Overall Height:
2.538 inches
Overall Width:
0.650 inches
Bushing Length:
0.410 inches
Body Length:
0.950 inches
Body Width:
0.650 inches
Body Height:
1.104 inches
Case Material:
Plastic
Actuator Length:
0.750 inches
Actuator Style:
Rectangular
Actuator Height:
0.438 inches
Actuator Width:
0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Features Provided:
Actuator seal

NSN 5930-00-486-7194Push Switch - Page 2 of 2



Thready Qty Per Inch (tpi):
32
Thread Size:
0.562 inches
Nonpile-up Contact Arrangement:
6 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.000 amperes inductive dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac
Special Features:
One terminal for lamp
Thread Series Designator:
Un
Terminal Type And Quantity:
19 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0