## NSN 5930-00-487-0014

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-487-0014

Hazardous Locations/environmental Protection:
Shock resistant and vibration resistant
Overall Height:
1.875 inches
Overall Width:
1.469 inches
Body Thickness:
0.132 inches
Unthreaded Mounting Hole Diameter:
0.130 inches single mounting facility
Distance Between Mounting Facility Centers:
1.562 inches single mounting facility
Operating Tempurature Range:
-65.0/+85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
2 single section rear
Mounting Method:
Strut single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
contact venage ranning in vener
30.0 dc at sea level
30.0 dc at sea level
30.0 dc at sea level  Mounting Facility Pattern:
30.0 dc at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility
30.0 dc at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Terminal Type:
30.0 dc at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Terminal Type:  Clip
30.0 dc at sea level  Mounting Facility Pattern:  Two position in-line single mounting facility  Terminal Type:  Clip  Contact Switching Action:
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip  Contact Switching Action: Breaks before makes single section rear
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip Contact Switching Action: Breaks before makes single section rear Contact Load Current Rating:
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip  Contact Switching Action: Breaks before makes single section rear  Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip  Contact Switching Action: Breaks before makes single section rear  Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level  Style Designator:
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip Contact Switching Action: Breaks before makes single section rear Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level  Style Designator: Switch section, rotary
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip  Contact Switching Action: Breaks before makes single section rear  Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level  Style Designator: Switch section, rotary  Shelf Life:
Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Breaks before makes single section rear Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level Style Designator: Switch section, rotary Shelf Life: N/a
Mounting Facility Pattern: Two position in-line single mounting facility Terminal Type: Clip Contact Switching Action: Breaks before makes single section rear Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level Style Designator: Switch section, rotary Shelf Life: N/a
30.0 dc at sea level  Mounting Facility Pattern: Two position in-line single mounting facility  Terminal Type: Clip  Contact Switching Action: Breaks before makes single section rear  Contact Load Current Rating: 50.0 milliamperes resistive load ac at sea level  Style Designator: Switch section, rotary  Shelf Life: N/a  Unit Of Measure:

A052b0