## NSN 5930-00-488-3541

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-488-3541

g
Body Style:
Bushing mount
Hazardous Locations/environmental Protection:
Dustproof
Bushing Length:
0.470 inches
Body Length:
1.640 inches
Body Width:
1.320 inches
Body Height:
1.100 inches
Actuator Style:
Round
Actuator Diameter:
0.420 inches
Actuator Height:
1.050 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained
Actuator Position-locking Relationship:
Up position no locking action and down position locked in
Maximum Voltage Rating In Volts:
230.0 ac and 250.0 dc
End Application:
Los angeles class ssn, nimitz class, forrestal class
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded bushing
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch uni
Criticality Code Justification:
Feat
Contact Load Comment Bather At Mandager Bath 1971

## **Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

## **Special Features:**

Weapon system essential

## **NSN 5930-00-488-3541** Toggle Switch - Page 2 of 2



Inread Series Designator:
Uns
Terminal Type And Quantity:
12 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0