

View Online at <https://aerobasegroup.com/nsn/5930-00-488-7076>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

Between 0.766 inches and 0.796 inches

**Body Width:**

0.265 inches

**Body Height:**

Between 0.346 inches and 0.366 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.092 inches

**Actuator Height:**

0.048 inches

**Actuator Free Position Height:**

0.350 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

3.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.003 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac

**Special Features:**

Thread wrapped around normally closed term.

**Terminal Type And Quantity:**

2 wire lead and 1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0