## NSN 5930-00-488-9136

Push Switch - Page 1 of 2

**Terminal Type And Quantity:** 

6 tab, solder lug

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-00-488-9136

Panel mount
Hazardous Locations/environmental Protection:
Corrosion resistant and fungus resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant
Overall Length:
1.000 inches
Overall Height:
2.550 inches
Overall Width:
0.750 inches
Body Length:
0.650 inches
Body Width:
0.750 inches
Body Height:
2.023 inches
Case Material:
Metal
Actuator Length:
0.830 inches
Actuator Style:
Rectangular
Actuator Height:
0.170 inches
Actuator Width:
0.580 inches
Actuator Color:
Gray single actuator
Illuminated Actuator Color:
Green single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Uninclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 5.000 amperes inductive dc and 2.500 amperes lamp dc and 5.000 amperes inductive ac and 2.000
amperes lamp ac
Precious Material And Location:
Contacts gold

## NSN 5930-00-488-9136

Push Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0