# NSN 5930-00-489-0223

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-489-0223

## **Thread Class:**

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.328 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

0.938 inches

#### Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

#### Shaft Length:

0.750 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

# Nonturn Device Type:

Tab at 3: 00 o'clock

# **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section front

## **Throw Quantity:**

5 single section rear

## Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## **Rotor Through Connection Quantity:**

1 single section

# Switch Actuator Indexing Position Quantity:

5 single actuator

#### Shaft Type:

Round single actuator

# **Terminal Type:**

Tab, solder lug

# NSN 5930-00-489-0223

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

# Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0