

View Online at <https://aerobasegroup.com/nsn/5930-00-489-0349>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Shock proof and vibration resistant

**Overall Length:**

1.340 inches

**Overall Height:**

2.580 inches

**Overall Width:**

0.910 inches

**Bushing Length:**

0.490 inches

**Body Length:**

1.340 inches

**Body Width:**

0.910 inches

**Body Height:**

1.120 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.240 inches

**Actuator Height:**

0.720 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

57.5 ac and 14.0 dc

**Mounting Surface To Terminal End Distance:**

1.370 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded hole

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

9.000 amperes resistive dc and 5.000 amperes inductive dc and 2.500 amperes lamp dc and 6.500 amperes resistive ac and 4.000 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0