

View Online at <https://aerobasegroup.com/nsn/5930-00-489-0349>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Shock proof and vibration resistant

Overall Length:

1.340 inches

Overall Height:

2.580 inches

Overall Width:

0.910 inches

Bushing Length:

0.490 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

1.120 inches

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.720 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Maximum Voltage Rating In Volts:

57.5 ac and 14.0 dc

Mounting Surface To Terminal End Distance:

1.370 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

9.000 amperes resistive dc and 5.000 amperes inductive dc and 2.500 amperes lamp dc and 6.500 amperes resistive ac and 4.000 amperes inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0