Dust And Moisture Seal Boot - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-489-1369

Pai         Trace longh:         C028 inclusion         Hzardous Locations/environmental Protection:         Varialitythema lope 4         Overall lenght:         Quarity Dovice Quantity:         1         Saling Method:         Compression         Balang Method:         Ox98 inclusion         Quality Dovice Quantity:         1         Saling Method:         Ox98 inclusion         Quality Dovice Quantity:         Quality Dovice Quantity:         Quality Dovice Quantity:         Quarity Dovice Quantity:         Quarity Dovice Quantity:         Quarity Dovice Quantity:         Quantity Dovice Quantity:         Quarity Dovice Quantity:         Parced Dover <t< th=""><th>Thread Class</th><th>S:</th></t<>	Thread Class	S:
0.778 inches         Paradous Locations/environmental Protection:         Vatartight-ment type 4         Overall relight:         0.270 inches         Munting Device Quantity:         1         Sealing Method:         Corporation         Base Height:         0.089 inches         With Across Flats:         0.098 inches         Watting Method:         1.037 inches         Mounting Method:         1.048 inches         0.098 inches         Watting Method:         1.038 inches         Mounting Method:         1.049 interester         0.062 inches         Thread Stree:         1.035 inches         Matting Method:         1.049 interester         0.052 inches         Thread Stree:         1.049         Thread Stree:         0.250 inches         Base Thread Location (includes engineering type bulletins, brochures, etc., that relifed specification type data in specification formation and performance requirements and test conditions that are shown as "typicat", "average", ", etc.):         For Lobal Document:         Switch, toggle         Switch, toggle         Switch, to	2b	
Haradous Locations/environmental Protection:         Versal Height:         0.270 index         1020 index         0.370 index         Gamma type 4         Monting Device Quantity:         1         Seafing Method:         Compression         Dask height:         0.375 index         With Across Flats:         0.375 index         Outge Interded nut         Opening Interded nut         Outge Interded nut         Interde State:         Interde State:         Interde State:         Interde State:         Interde Interdet Nut         Reterdet State:         Interdet State:         Interdet State:         Interdet State:         Interdet State:         Interdet State:	Thread Leng	th:
Wateright-nema type 4         Versall Height:         0.270 inches         Mounting Device Quantity:         1         Saling Method:         Compression         Base Height:         0.088 inches         Watering Method:         Interest Flats:         0.375 inches         Mounting Method:         Inlegral fixeded nut         Opening Inside Diameter:         0.028 inches         Toread Sories:         Urst         17         Res Height:         0.250 inches         Toread Sories:         10.251 inches         Paread Sories:         10.250 inches         Sories:         10.250 inches         Base Height:         10.250 inches         Sories:         10.250 inches         Base Toread Location:         Internal         Rebersitione body         Style Designator:         Internal         Stabelines: body         Style Designator:         Internal         Base Height: body/style Sories         Style Designator:         Internal <th>0.078 inches</th> <td></td>	0.078 inches	
Overall Height:         0.200 inclos         Muning Device Quantity:         1         Sealing Method:         Compression         Base Height:         0.068 inches         With Across Flats:         0.307 inches         Mouning Method:         Integral threaded nut         Opening Inside Diameter:         0.408 inches         Thread Series:         Uns         Thread Series:         0.250 inches         Thread Series:         0.261 inches         Thread Series:         0.250 inches         Thread Series:         0.250 inches         Thread Series:         0.250 inches         Sea Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Intru-hole         Testal Documentical catalogs, industry directories, and similar trade publications, reflecting general type data on certain         Intru-hole         Style Designator:         Istal-Mit-Se423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain         Intru-hole	Hazardous L	ocations/environmental Protection:
0.270 inchos         9         200 inchos         0.ompression         Base Height:         0.038 inchos         Width Across Flats:         0.375 inchos         Mouning Method:         0.367 inchos         Opening Inside Diameter:         0.062 inchos         Thread Series:         0.062 inchos         Thread Series:         0.365 inchos         Thread Series:         0.365 inchos         Thread Series:         0.362 inchos         Thread Series:         0.362 inchos         Base Thread Location:         Internal         Material:         Rubber silicone body         Spite bried         Stab Document:         Industro Documential and performance requirements and test conduitors that are shown as "typical", "average", "", etc.):         For April         Swith, toggie         Swith, toggie         Swith, toggie         Theil Measure:         Na         Internat:         Internat:         Internat:         Internat:         Materia:         Store Documentia: <th>Watertight-ne</th> <td>ma type 4</td>	Watertight-ne	ma type 4
Houning Device Quantity:         1         Seafing Method:         Compression         Base Height:         Queb Enchos         Hinder Stress         Quity Across Flass:         Quity Across Flass:         Queb Enchos         Inlegal threaded nut         Opening Inside Diameter:         Queb Enchos         Thread Series:         Queb Encho         Insert         Thread Series:         Queb Encho(pt):         40         Thread Stac         Base Fload Location:         Internal         Paried Series:         Queb Fload Cocation:         Internal         Paried Series:         Queb Fload Cocation:         Internal         Paried Series:         Queb Fload Series:         Paried Series:         Queb Fload Series:         Queb Fload Series:         Paried Series:	Overall Heigl	ht:
1         Sealing Method:         Compression         Base Height:         0.098 inches         Witch Across Flats:         0.375 inches         Mounting Method:         Integralt threaded nut         Opening Inside Diameter:         0.062 inches         Thread Series:         Uns         Thread Strees:         0.205 inches         Base Thread Location:         Interral         Material:         Rubber silicone body         Style paignator:         Thread Strees:         Interral         14         Material:         Rubber silicone body         Style pasignator:         Thread Strees:         Intra-distance:         Style pasignator:         Intru-hole	0.270 inches	
Sealing Method:         Compression         Base Meight:         Code incluss         Outsing Method:         Code incluss         Muthing Method:         Integral threaded nut         Obd2 incluss         Outsign Method:         Integral threaded nut         Obd2 incluss         Monting Method:         Integral threaded nut         Obd2 incluss         Thread Series:         Uns         Thread Stree:         O250 incluss         Base Thread Location:         Interned!         Rubers illicone body         Sple Designator:         Thrushel         Particulation:         Internel         Muthol:         Sple Designator:         Thrushel         Fact Application functicules engineering type bulletins, brochures, etc., that reflect specification type data on certain inviccules commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain inviccules and function industry directories, and similar trade publications, reflecting general type data on certain inviccules and function industry directories, and similar trade publications, reflecting general type data on certain inviccules and function industry directories, and similar trade publications, reflecting general type data on certain invicule	Mounting De	evice Quantity:
Compression         Base Height:         Compression         Base Height:         Compression         Width Across Flats:         Control Method:         Integral threaded nut         Prend Diameter:         Code Control Method:         Integral threaded nut         One Control Method:         Integral State         Control State         OL20 Inches         Interned State         Outcotter         OL20 Inches         Distroad Location:         Interned         Matchai:         Rubber Silcone body         Style Designator:         Intru-Method:         Internet:         Auduets commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmetal and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         For Applicatin Data:         Nametone	1	
Base Height:         0.008 inches         Vidth Across Flats:         0.375 inches         Monning Method:         Integral threaded nut         Opening Inside Diameter:         0.062 inches         Thread Stries:         0.762 inches         Thread Stries:         0.763 Okt Per Inch (tpi):         40         Thread Stries:         0.250 inches         Base Thread Location:         1 Internal         Material:         Rubers Silicone body         Syle Designator:         Intru-hole         Parte Aba Document:         Intru-hole         Stable Document:         Vide Across Consercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification type data in specificatin type data in specification type data in spec	Sealing Meth	nod:
0.098 indes         Width Across Flats:         0.375 inches         Muntrig Method:         Integral threaded nut         Opening Inside Diameter:         0.002 inches         Thread Stries:         Uns         Thread Stries:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         B1349-mill-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ty	Compression	
With Across Flats:         0.375 Inches         Nouring Method:         Incerpaid Intreaded nut         Opening Inside Diameter:         0.062 Inches         Thread Series:         Inside Diameter (IP):         40         Thread Series:         0.525 Inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Structure:         1349-mill-bs423 specification (Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification includes engineering type bulletins, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Fe Application Data:         Nat         Internal:         Nat         Disclation:         Indiction:         Indiction:         Indiction Data:         State, toggie         Shell, tife:         Na         Indiction:         Indiction:         Indiction:         Indiction:         Indiction:         Indiction:         Indiction:         Indiction: </td <th>Base Height:</th> <td></td>	Base Height:	
<ul> <li>9.375 inches</li> <li>Mouting Method:</li> <li>Inegral threaded nut</li> <li>Opening Inside Diameter:</li> <li>Que Inches</li> <li>Thread Series:</li> <li>Thread Series:</li> <li>Thread Stries:</li> <li>Opening Inside Diameter:</li> <li>Que Inch (tpi):</li> <li>Au</li> <li>Thread Stries:</li> <li>Que Inches</li> <li>Thread Stries:</li> <li>Que Inches</li> <li>Autor Stries:</li> <li>Autor Manauer equirements and test conditions that are shown as "tpical", "average", ", etc.):</li> <li>Autor Measure:</li> <li>Autor Measure:</li></ul>	0.098 inches	
Mounting Method:         Integral threaded nut         Integral threaded nut         Opening Inside Diameter:         0.002 inches         Thread Series:         Ins         Thread y the Inch (tpl):         40         Thread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Poble silicone body         Syle Designator:         Thru-hole         Thru-hole         Pase Jase Serie:         Informati, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fourith, toggle         Sheft Life:         Na         InterNote         Fourith, toggle         Sheft Life:         Na         InterNote         Inter	Width Acros	s Flats:
Integral threaded nut         Opening Inside Diameter:         0.062 inches         Thread Series:         Uns         Thready Qty Per Inch (tpi):         40         Thread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         1343-9mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification rup entait and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Fise Application Data:         Switch, toggie         Shift Life:         Inder         Fixed         Interfact         Fixed Data:         Interfact         Tort-hole         Fixed Data:         Interfact Data:	0.375 inches	
Spening Inside Diameter:         0.062 inches         Inread Series:         Uns         Thready Cty Per Inch (tpi):         40         Foread Size:         0.250 inches         Base Thread Location:         Internal         Version body         Style Designator:         Thru-hole         Fast Data Document:         S1349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Factplication Data:         Switch, toggle         Shift Life:         Intor Measure:         Intor Measure:         Intor Measure:         Intor Measure:         Intor Measure:	Mounting Me	ethod:
<ul> <li>0.062 inches</li> <li>Irread Series:</li> <li>Uns</li> <li>Irready Qty Per Inch (tpi):</li> <li>40</li> <li>Irread Size:</li> <li>0.250 inches</li> <li>Base Thread Location:</li> <li>Internal</li> <li>Material:</li> <li>Ruber silicone body</li> <li>Style Designator:</li> <li>Thru-hole</li> <li>Test Data Document:</li> <li>81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.).</li> <li>Fsc Application Data:</li> <li>Switch, toggle</li> <li>Shelf Life:</li> <li>N/a</li> <li>Int of Measure:</li> <li>-</li> <li>Test Cata Commental Catalogs, industry directories, and similar trade publications, reflecting general type data in specification type data in specification type data in specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.).</li> <li>Fisc Application Data:</li> <li>N/a</li> <li>Int of Measure:</li> <li>- Commental Catalogs, industry directories, and similar trade publications, reflecting type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.).</li> </ul>	Integral thread	ded nut
IneadSeries:         Uns         Ineady Oty Per Inch (tpl):         40         Thread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Part Data Document:         N349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Na         Int of Measure:         Int of Measure:         Image:         Image: <td< td=""><th>Opening Insi</th><td>ide Diameter:</td></td<>	Opening Insi	ide Diameter:
Uns         Tready Qty Per Inch (tpi):         40         Tread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         N349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fox Application Data:         Na         Inter file:         Inter file: <th>0.062 inches</th> <td></td>	0.062 inches	
Interady Qty Per Inch (tpi):         40         Interad Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Thru-hole         Style-Style Style Commercial catalogs, industry directories, and similar trade publications, reflecting general type data in specification (protectories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         For Application Data:         Switch, toggle         Shelf Life:         N/a         Unit Of Measure:         Image:         Image:<	Thread Serie	es:
40         Fread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thruhole         Thruhole         Style Designation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fac Application Data:         Switch, toggle         Sheft Life:         Na         Int Of Measure:         Int Of Measure:         Image:	Uns	
Thread Size:         0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification of includes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Sheft Life:         Inder Masure:         Image:	Thready Qty	Per Inch (tpi):
0.250 inches         Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Sheft Life:         Inter Commential catalogs         Inter Commential catalogs         Material         Material         Built fire:         Inter Commential catalogs         Inter Comparison         Inter Comparison         Inter Comparison         Inter Commential catalogs         Inter Comparison         Inter Commential catalogs         Inter Commential catalogs         Inter Commential catalogs         Inter Commential ca	40	
Base Thread Location:         Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Sheft Life:         Inter Of Measure:         -         Thru-Fole:         Thru-Fole:         Internation:	Thread Size:	
Internal         Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         Format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Sheff Life:         N/a         Unit Of Measure:            Demilitrization:	0.250 inches	
Material:         Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Shelf Life:         N/a         Unit Of Measure:            militarization:	Base Thread	Location:
Rubber silicone body         Style Designator:         Thru-hole         Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:	Internal	
Style Designator: Thru-hole Test Data Document: 81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Fsc Application Data: Switch, toggle Shelf Life: N/a Unit Of Measure: - Demilitarization:	Material:	
Thru-hole Test Data Document: 81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Fsc Application Data: Switch, toggle Shelf Life: N/a Unit Of Measure: Demilitarization:	Rubber silicor	ne body
Test Data Document:         81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Fsc Application Data:         Switch, toggle         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:	Style Design	ator:
81349-mil-b-5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Fsc Application Data: Switch, toggle Shelf Life: N/a Unit Of Measure: Demilitarization:	Thru-hole	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Fsc Application Data: Switch, toggle Shelf Life: N/a Unit Of Measure: 	Test Data Do	ocument:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Fsc Application Data: Switch, toggle Shelf Life: N/a Unit Of Measure:  Demilitarization:	81349-mil-b-5	5423 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Fsc Application Data:   Switch, toggle   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	format; exclu	des commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Switch, toggle Shelf Life: N/a Unit Of Measure: Demilitarization:	environmenta	I and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure:  Demilitarization:	Fsc Applicat	ion Data:
N/a Unit Of Measure:  Demilitarization:	Switch, toggle	
Unit Of Measure:  Demilitarization:		
 Demilitarization:		
Demilitarization:	Unit Of Meas	sure:
No		ion:
	No	

## NSN 5930-00-489-1369

Dust And Moisture Seal Boot - Page 2 of 2

**Fiig:** A02000

