

View Online at <https://aerobasegroup.com/nsn/5930-00-489-2847>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Body Diameter:

1.000 inches

Bushing Length:

0.540 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.600 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Incl 28v dc holding coil

Thread Series Designator:

Uns

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0