

View Online at <https://aerobasegroup.com/nsn/5930-00-489-2853>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Body Diameter:

1.000 inches

Bushing Length:

0.540 inches

Body Length:

1.850 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

Between 1.530 inches and 1.590 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary

Actuator Position-locking Relationship:

Up position locked in and down position no locking action

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Holding solenoid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.468 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.000 amperes lamp dc and 4.000 amperes motor dc

Special Features:

Incl 28v dc holding coil

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0