

View Online at <https://aerobasegroup.com/nsn/5930-00-489-7650>

Thread Class:

2b 1st mounting facility

Thread Length:

0.063 inches 2nd mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.875 inches

Overall Height:

2.812 inches

Overall Width:

2.812 inches

Shaft Length:

1.313 inches single actuator

Individual Section Quantity:

7

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

A

Longest Horizontal Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.297 inches 1st mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

11 each section rear

Mounting Method:

Threaded bushing w/panel seal 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.625 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Rectangular/square, threaded hole single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

7.5 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unef 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0