## NSN 5930-00-490-4505

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-490-4505
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and salt spray resistant
Overall Length:
0.740 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Body Height:
1.960 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
1.000 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Amber single actuator
Actuator Inscription:
Cmptr load single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Holding solenoid
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Dating At Maximum Dated Voltage

Contact Load Current Rating At Maximum Rated Voltage:
5 000 amperes resistive do and 2 500 amperes industive do and

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

## **NSN 5930-00-490-4505**Push Switch - Page 2 of 2



Precious Material And Location:
Contact surfaces gold and contacts silver
Unable To Decode:
Unable to decode and unable to decode
Terminal Type And Quantity:
17 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A053a0