## NSN 5930-00-490-8812

Thermostatic Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-490-8812

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.203 inches
Overall Height:
0.276 inches
Body Diameter:
0.625 inches
Mounting Slot Width:
0.140 inches
Body Height:
0.256 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and slot and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
6.0 amperes resistive load third voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
135.00 actuation point degrees fahrenheit and 145.00 actuation point degrees fahrenheit and 123.00 deactuation point degrees fahrenheit
and 133.00 deactuation point degrees fahrenheit and 12.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level third voltage
Media For Which Designed:
Gas or liquid
Style Designator:
Disc w/flange
Shelf Life:

## NSN 5930-00-490-8812

Thermostatic Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0