

View Online at <https://aerobasegroup.com/nsn/5930-00-490-8813>

Body Style:

Bushing mount

Bushing Length:

0.352 inches

Body Length:

0.652 inches

Body Width:

0.500 inches

Body Height:

0.415 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.115 inches

Actuator Height:

0.400 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 24.0 dc

End Application:

Spruance class dd (963), ticonderoga class cg (47), torpedo adcap 48, los angeles class ssn (688), deep submergence systems programs (dssp), missile all-weather anti-ship harpoon (agm-84), ac-130a, ac-130h, mc-130h, ec-130e

Mounting Surface To Terminal End Distance:

0.571 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Thread Series Designator:

Uns

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0