

View Online at <https://aerobasegroup.com/nsn/5930-00-490-8813>

**Body Style:**

Bushing mount

**Bushing Length:**

0.352 inches

**Body Length:**

0.652 inches

**Body Width:**

0.500 inches

**Body Height:**

0.415 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.115 inches

**Actuator Height:**

0.400 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 24.0 dc

**End Application:**

Spruance class dd (963), ticonderoga class cg (47), torpedo adcap 48, los angeles class ssn (688), deep submergence systems programs (dssp), missile all-weather anti-ship harpoon (agm-84), ac-130a, ac-130h, mc-130h, ec-130e

**Mounting Surface To Terminal End Distance:**

0.571 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

3 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0