

View Online at <https://aerobasegroup.com/nsn/5930-00-491-2340>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Bushing Length:

Between 0.375 inches and 0.385 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.490 inches and 0.510 inches

Body Height:

0.406 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.050 inches

Actuator Height:

Between 0.349 inches and 0.369 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.438 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Un

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0