

View Online at <https://aerobasegroup.com/nsn/5930-00-491-2369>

Body Style:

Bushing mount

Overall Height:

2.250 inches

Bushing Length:

Between 0.375 inches and 0.385 inches

Body Length:

0.643 inches

Body Width:

0.549 inches

Body Height:

Between 0.905 inches and 0.915 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Height:

Between 0.755 inches and 0.765 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

Aircraft: hawkkeye e-2c, c-2a, and prowler ea-6b; helicopter: mh-53e, and sea king h-3

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 4.000 amperes motor dc

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0