

View Online at <https://aerobasegroup.com/nsn/5930-00-491-3586>

Overall Length:

3.125 inches

Power Cable Length:

24.000 inches

Ac Voltage Rating:

50.0 volts

Dc Voltage Rating:

50.0 volts

Frequency Rating:

60.0 hertz

Overall Diameter:

2.135 inches

Actuation Method:

Buoyancy

Electrical Connection Type:

Cable

Internal Battery Accommodation:

Not included

Current Rating At Maximum Rated Voltage:

40.0 milliamperes load

Voltage Rating At Maximum Rated Current:

50.0 volts

Float Quantity:

1

Operating Temperature Rating:

Between 0.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Thread

Mounting Position:

Vertical

Maximum Current Rating:

200.0 milliamperes load

Contact Arrangement:

Spst herm sealed mag actuated snap-action make and break n.O. Or n.C. By inverting float

Relay:

Not included

Liquid Type For Which Designed:

Various fuels

Float Effective Travel:

2.500 inches

Mounting Dimensions:

Mtd by 0.250nptmale thd w/0.625 hex nut to lock position

Tank Insertion Length:

2.625 inches

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T109-d