

View Online at <https://aerobasegroup.com/nsn/5930-00-491-6556>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

0.690 inches

**Body Height:**

1.160 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Length:**

0.828 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.250 inches

**Actuator Roller Diameter:**

0.370 inches

**Actuator Roller Width:**

0.160 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

10.0 ounces

**Actuator Movement:**

0.078 pretravel inches and 0.094 overtravel inches and 0.008 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0