

View Online at <https://aerobasegroup.com/nsn/5930-00-491-8705>

**Thread Class:**

2b 2nd mounting facility

**Thread Length:**

0.344 inches 1st mounting facility and 0.375 inches 1st mounting facility

**Overall Length:**

Between 4.500 inches and 4.564 inches

**Overall Height:**

2.266 inches

**Overall Width:**

2.266 inches

**First Flat Length:**

0.427 inches single actuator and 0.447 inches single actuator

**Flat Height:**

0.216 inches single actuator and 0.220 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.595 inches single actuator

**Distance Between Mounting Facility Centers:**

1.495 inches 2nd mounting facility and 1.505 inches 2nd mounting facility

**Individual Section Quantity:**

3

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

24 each section rear

**Mounting Method:**

Threaded hole 2nd mounting facility

**Thready Qty Per Inch (tpi):**

32 2nd mounting facility

**Thread Size:**

0.375 inches 1st mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Two position in-line 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Pin

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Square wafer, panel mount

**Thread Series Designator:**

Unef 1st mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0