NSN 5930-00-491-8833



Push Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-00-491-8833 **Body Style:** Panel mount **Hazardous Locations/environmental Protection:** Moisture proof **Body Diameter:** 0.562 inches **Body Length:** 1.031 inches **Actuator Diameter:** Between 0.355 inches and 0.395 inches **Actuator Height:** 0.250 inches **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Features Provided:** Actuator seal **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, double make, momentary action single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc and 3.000 amperes inductive dc and 3.000 amperes lamp dc and 10.000 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac **Special Features:** Press mtd and retained b screw **Test Data Document:** 81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 tab w/screw Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A053a0

No