

View Online at <https://aerobasegroup.com/nsn/5930-00-491-9075>

Overall Length:

5.188 inches

Overall Width:

2.812 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

2.406 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

3.625 inches

Bulb Diameter:

0.688 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -265.0 degrees fahrenheit and 195.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

6.5 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+120.00/+210.00 actuation point degrees fahrenheit and +120.00/+210.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

230.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0