NSN 5930-00-493-1226

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-493-1226

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 2.086 inches **Overall Height:** 1.031 inches **Overall Width:** 1.094 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.875 inches single actuator **Individual Section Quantity: Operating Tempurature Range:** -65.0/+125.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section front **Throw Quantity:** 2 each section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 300.0 highest ac voltage rating at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:** 60.0 degrees single actuator

Detent Rotational Torque Range:

+1.000/+6.000 inch-pounds single actuator

NSN 5930-00-493-1226

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device 1	Ivpe) :
-------------------------------	------	------------

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0