

View Online at <https://aerobasegroup.com/nsn/5930-00-493-5882>

**Thread Length:**

0.457 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.919 inches

**First Flat Length:**

0.270 inches single actuator

**Flat Height:**

0.223 inches single actuator

**Shaft Diameter:**

0.251 inches single actuator

**Shaft Length:**

0.914 inches single actuator

**Overall Diameter:**

1.185 inches

**Nonturn Device Radius:**

0.390 inches at 3: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

195.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+8.000/+115.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0