NSN 5930-00-494-6015

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-494-6015

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

6.230 inches

Overall Height:

3.100 inches

Overall Width:

4.750 inches

Body Length:

3.200 inches

Body Width:

4.100 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Longest Horizontal Distance Between Mounting Centers:

4.250 inches

Longest Vertical Distance Between Mounting Centers:

3.100 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage

NSN 5930-00-494-6015

Pressure Switch - Page 2 of 2



Contact Adjustability: Deactuation point adjustable and actuation point adjustable Contact Adjustment Range: +200.00/+3000.00 actuation point pounds per square inch and +100.00/+2800.00 deactuation point pounds per square inch Contact Adjustment Type: Internal actuation point serrated nut and internal deactuation point serrated nut Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: Double compression, threaded internal single connection Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0