

View Online at <https://aerobasegroup.com/nsn/5930-00-496-6928>

**Hazardous Locations/environmental Protection:**

Dustproof and moisture proof

**Overall Length:**

1.342 inches

**Overall Height:**

0.555 inches

**Body Diameter:**

0.590 mils and 0.610 centimeters

**Body Height:**

0.305 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.158 inches and 0.168 inches

**Distance Between Mounting Facility Centers:**

1.062 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

6.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

228.00 actuation point degrees fahrenheit and 212.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

30.0 dc at sea level second voltage

**Special Features:**

4.000 in. Lg wire leads

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Liquid

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0