

View Online at <https://aerobasegroup.com/nsn/5930-00-496-6928>

Hazardous Locations/environmental Protection:

Dustproof and moisture proof

Overall Length:

1.342 inches

Overall Height:

0.555 inches

Body Diameter:

0.590 mils and 0.610 centimeters

Body Height:

0.305 inches

Unthreaded Mounting Hole Diameter:

Between 0.158 inches and 0.168 inches

Distance Between Mounting Facility Centers:

1.062 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -30.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

6.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

228.00 actuation point degrees fahrenheit and 212.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Special Features:

4.000 in. Lg wire leads

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0