

View Online at <https://aerobasegroup.com/nsn/5930-00-496-9435>

Thread Class:

2a single mounting facility

Thread Length:

0.344 inches single mounting facility and 0.406 inches single mounting facility

Overall Length:

Between 4.531 inches and 4.593 inches

Overall Height:

Between 2.281 inches and 2.343 inches

Overall Width:

Between 1.907 inches and 1.969 inches

First Flat Length:

0.281 inches single actuator and 0.343 inches single actuator

Flat Height:

0.213 inches single actuator and 0.219 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.344 inches single actuator and 0.406 inches single actuator

Nonturn Device Radius:

0.500 inches at 9: 00 o'clock and 0.562 inches at 9: 00 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

14 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

18 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Special Features:

Three dummy terminals on front and rear all sections

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0