

View Online at <https://aerobasegroup.com/nsn/5930-00-496-9435>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.344 inches single mounting facility and 0.406 inches single mounting facility

**Overall Length:**

Between 4.531 inches and 4.593 inches

**Overall Height:**

Between 2.281 inches and 2.343 inches

**Overall Width:**

Between 1.907 inches and 1.969 inches

**First Flat Length:**

0.281 inches single actuator and 0.343 inches single actuator

**Flat Height:**

0.213 inches single actuator and 0.219 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.344 inches single actuator and 0.406 inches single actuator

**Nonturn Device Radius:**

0.500 inches at 9: 00 o'clock and 0.562 inches at 9: 00 o'clock

**Individual Section Quantity:**

7

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

14 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

135.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

18 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

20.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

1.5 amperes resistive load dc at sea level

**Special Features:**

Three dummy terminals on front and rear all sections

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0