NSN 5930-00-497-0934

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-497-0934

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.688 inches

Overall Height:

1.188 inches

Overall Width:

1.188 inches

First Flat Length:

0.218 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

12 single actuator

NSN 5930-00-497-0934Rotary Switch - Page 2 of 2

A052b0



| Shaft Type: |
|---|
| Round, flatted single actuator |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes single section front |
| Switch Actuator Positioning Increment: |
| 30.0 degrees single actuator |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load dc at sea level |
| Style Designator: |
| Square wafer, panel mount |
| Test Data Document: |
| 81349-mil-s-3786/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unef single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |