## NSN 5930-00-497-4501

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-497-4501 **Body Style:** Hole mounted **Overall Length:** 4.020 inches **Overall Height:** 2.500 inches **Overall Width:** 1.550 inches **Housing Height:** 1.790 inches **Housing Length:** 4.020 inches **Housing Width:** 1.550 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 2.350 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.170 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.190 inches **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Switch Actuating Force:** 64.0 inch-ounces **Actuator Movement:** 10.0 pretravel degrees and 80.0 overtravel degrees and 4.0 differential degrees **Contact Load Current Rating At Maximum Rated Voltage:** 110.000 milliamperes resistive dc and 110.000 milliamperes inductive dc and 1.200 amperes resistive ac and 1.200 amperes inductive ac **Special Features:** Less actuator lever **Precious Material And Location:** Contacts silver

8 screw

Unc

**Thread Series Designator:** 

**Terminal Type And Quantity:** 

## NSN 5930-00-497-4501

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0