## NSN 5930-00-497-5278



Sensitive Switch - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5930-00-497-5278 **Body Style:** Hole mounted **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.375 inches **Body Length:** Between 0.761 inches and 0.791 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.346 inches and 0.366 inches **Unthreaded Mounting Hole Diameter:** Between 0.087 inches and 0.090 inches **Switch Actuator Quantity: Actuator Style:** Round **Maximum Voltage Rating In Volts:** 30.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 1.0 ounces **Switch Actuating Force:** Between 3.0 ounces and 5.0 ounces **Actuator Movement:** Between 0.020 pretravel inches and 0.005 overtravel inches and 0.004 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc and 0.500 milliamperes inductive dc **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A053a0