NSN 5930-00-497-5558

Pressure Switch - Page 1 of 2

Thread Class:

Inside Diameter:

Overall Length: 4.500 inches Overall Height:

2b single pressure connection

0.438 inches single connection



View Online at https://aerobasegroup.com/nsn/5930-00-497-5558

2.875 inches
Overall Width:
5.250 inches
Body Length:
2.500 inches
Body Width:
4.875 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Differential
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
3.2 amperes resistive load first voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+16.00/+160.00 actuation point pounds per square inch gage and +16.00/+160.00 deactuation point pounds per square inch gage

NSN 5930-00-497-5558

Pressure Switch - Page 2 of 2



Contact	Δd	justment	Tv	ne'
Contact	Au.	Justinent	ı y	ŊΦ.

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

550.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0