NSN 5930-00-497-7638

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-497-7638

Body Style:
Hole mounted
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
0.969 inches
Actuator Free Position Height:
Between 1.689 inches and 1.749 inches
Housing Length:
2.440 inches
Housing Width:
1.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
Between 0.996 inches and 1.004 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 22.0 ounces and 39.0 ounces
Actuator Movement:
Between 0.078 pretravel inches and 0.219 overtravel inches and 0.005 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

NSN 5930-00-497-7638

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A053a0