## NSN 5930-00-497-7639

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-497-7639

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.921 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.142 inches
Actuator Style:
Round
Actuator Diameter:
0.328 inches
Actuator Height:
0.578 inches
Actuator Free Position Height:
Between 1.480 inches and 1.520 inches
Maximum Voltage Rating In Volts:
480.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 9.5 ounces
Actuator Movement:
Between 0.002 differential inches and 0.006 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a

## NSN 5930-00-497-7639

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0